

FARO® Laser Scanner Focus^{3D}



Intuitive touchscreen display

Control all scanner functions with a touch interface for unparalleled ease of use and control

Stand-alone solution

Ultraportable design allows for operation without external devices

Small and compact

With a size of only 24 x 20 x 10cm and a weight of just 5.0kg, the Focus^{3D} is the smallest 3D scanner ever built

Integrated colour camera

Photorealistic 3D colour scans due to an integrated colour camera featuring an automatic 70 megapixels parallax-free colour overlay

High-performance battery

Integrated lithium-ion battery provides up to five hours of battery life and can be charged during operation

Data management

All data is stored on a SD card enabling easy and secure transfer to a PC. Using SCENE WebShare images can be shared on the internet

FARO Focus^{3D}: Small, light, user-friendly

The Focus^{3D} is a high-speed 3D scanner for detailed measurement and documentation. The Focus^{3D} uses laser technology to produce incredibly detailed three-dimensional images of complex environments and geometries in only a few minutes. The Focus^{3D} has a touch operated screen to control scanning functions and parameters. The resulting image is an assembly of millions of 3D measurement points in colour which provides an exact digital reproduction of existing conditions.

A leap in innovation and efficiency to lower your costs

The Focus^{3D} offers the most efficient method for three-dimensional documentation of building construction, excavation volumes, façade and structural deformations, crime scenes, accident details, product geometry, factories, process plants and more. Given its minimal size and weight as well as touch interface, the Focus^{3D} is easy to work with and saves up to 50% of scan time compared to conventional scanners.

Benefits

- ▶ **Complete 3D documentation:** Suitable for documentation of large spaces, quality control of components and reverse engineering
- ▶ **Precise & fast:** Its millimetre-accuracy and its 976,000 measurement points/sec mean precise and efficient measurement
- ▶ **Economical:** Unsurpassed cost-value proposition make every scanning project economical
- ▶ **Easy:** Compact design and touch interface

FARO® Laser Scanner Focus^{3D}



Specifications

Ranging unit

Unambiguity interval: 153.49m (503.58ft)
Range Focus^{3D} 120¹: 0.6m - 120m indoor or outdoor with low ambient light and normal incidence to a 90% reflective surface
Range Focus^{3D} 20: 0.6m - 20m at normal incidence on >10% matte reflective surface
Measurement speed: 122,000 / 244,000 / 488,000 / 976,000 points/sec
Ranging error²: ±2mm at 10m and 25m, each at 90% and 10% reflectivity
Ranging noise³:
 @10m - raw data: 0.6mm @ 90% refl. | 1.2mm @ 10% refl.
 @10m - noise compressed⁴: 0.3mm @ 90% refl. | 0.6mm @ 10% refl.
 @25m - raw data: 0.95mm @ 90% refl. | 2.2mm @ 10% refl.
 @25m - noise compressed⁴: 0.5mm @ 90% refl. | 1.1mm @ 10% refl.

Colour unit

Resolution: Up to 70 megapixel colour
Dynamic colour feature: Automatic adaption of brightness

Deflection unit

Vertical field of view: 305°
Horizontal field of view: 360°
Vertical step size: 0.009° (40,960 3D pixels on 360°)
Horizontal step size: 0.009° (40,960 3D pixels on 360°)
Max. vertical scan speed: 5,820rpm or 97Hz


Laser (Optical transmitter)

Laser power (cw Ø): 20mW (Laser class 3R)
Wavelength: 905nm
Beam divergence: Typical 0.16mrad (0.009°)
Beam diameter at exit: 3.8mm, circular

Data handling and control

Data storage: SD, SDHC™, SDXC™; 32GB card included
Scanner control: Via touchscreen display

1) Depends on ambient light, which can act as a source of noise. Bright ambient light (e.g. sunshine) may shorten the actual range of the scanner to lesser distances. In low ambient light, the range can be more than 120m for normal incidence on high-reflective surfaces.
 2) Ranging error is defined as the maximum error in the distance measured by the scanner from its origin point to a point on a planar target.
 3) Ranging noise is defined as a standard deviation of values about the best-fit plane.
 4) A noise-compression algorithm may be activated to average points in sets of 4 or 16, thereby compressing raw data noise by a factor of 2 or 4.
 Subject to change without prior notice.



General

Power supply voltage: 19V (external supply), 14.4V (internal battery)
Power consumption: 40W and 80W respectively (while battery charges)
Battery life: Up to 5 hours
Ambient temperature: 5° - 40°C
Humidity: Non-condensing
Cable connector: Located in scanner mount

Weight: 5.0kg
Size: 240x200x100mm³
Maintenance calibration: Annual
Parallax-free: Yes
Dual-axes inclination sensor: Accuracy 0.015°; Range ±5°

FARO, THE MEASURE OF SUCCESS, FaroArm, Quantum, CAM2, ION, and FARO Laser ScanArm are registered trademarks and trademarks of FARO Technologies Inc. © 2010 FARO Technologies Inc. All Rights Reserved.



Protected by U.S. patents 7,430,068 B2 and 7,733,544.

Global Offices: Australia • Brazil • China • France • Germany • India • Italy • Japan • Malaysia • Mexico • Netherlands • Philippines • Poland
 Portugal • Singapore • Spain • Switzerland • Thailand • Turkey • United Kingdom • USA • Vietnam

www.faro.com ■ Free call 00 800 3276 7253 ■ info@faroEurope.com